

SONARtrac® Water and Wastewater Flow Measurement System

CiDRA's breakthrough SONARtrac flow measurement technology now delivers the same compelling price/performance combination to water and wastewater applications.

CiDRA's SONARtrac volumetric flow technology is the new paradigm for process flow measurement technology. The SONARtrac clamp-on system allows on-line volumetric flow measurement on virtually any type of pipe material and lined pipe, without any coupling gels or special adjustments.

SONARtrac measurement systems do not utilize ultrasonics; they employ patented sonar array processing techniques to listen to, and interpret, naturally occurring and coherent flow turbulence in process piping with a high degree of accuracy and repeatability.

Now you can experience the same high reliability, proven performance, and value of CiDRA's multiphase SONARtrac product flow technology on your water and wastewater applications with the SONARtrac Water and Wastewater Flow Measurement System.

Sonar Technology

CiDRA's SONARtrac technology represents an innovative new class of industrial measurement instrumentation. This sonar technology utilizes array processing techniques similar to those used in the field of sonar processing. CiDRA's proprietary sonar technology was initially developed for flow and compositional measurement in one of the world's most demanding environments: downhole, offshore oil and gas production. CiDRA has taken the proven reliability of its SONARtrac technology to provide new measurement capabilities and provide insight into the monitoring and optimization of industrial processes.

- Installs while process is running
- No pipe penetration, safe and easy to install
- No pressure restrictions
- Increased measurement accuracy and certainty
- Increased process efficiency and uptime
- Increased product quality

Advantages:

- Low power requirement
- Operation is not impacted by scaling, entrained air, chemicals and non-conductive fluids
- Lowest life-cycle cost
- Can be installed in a tight meter location
- No need for calibration or maintenance
- Meter can be validated annually while in place

Volumetric Flow for Municipal Water and Wastewater Applications

Flow Applications:

- Pump station
- Sludge
- Clean water
- Influent and effluent
- Recycled Activated Sludge (RAS)
- Waste Activated Sludge (WAS)



Features:

- ◆ Entirely non-contact, "wrap-around" flow sensor design
- ◆ Transmitter with integrated flow processor
 - Programmable by keypad or PC interface
 - Self-diagnostics capability
- ◆ Data logging capabilities
 - Volumetric flow
 - Flow Velocity
- ◆ USB Port and memory stick
 - Remote data logging retrieval
 - Flow diagnostic reporting to CiDRA technical support
- ◆ Analog /Digital Outputs
 - Two (2) 4-20 mA current outputs
 - Pulse output
 - Alarm output
 - HART® protocol
- ◆ Options
 - FOUNDATION Fieldbus™
 - PROFIBUS® PA
 - MODBUS®

Benefits:

- Accurate and reliable operation in water and wastewater applications and management
- Economic flow measurement for a wide variety of pipe sizes
- Compatible with most pipe materials and lined pipe
- Simple, quick installation, minimal surface preparation, no gel required, light weight
- Compact, low profile design

HART is a registered trademark of the HART Communications Foundation.
 FOUNDATION Fieldbus is a trademark of Fieldbus Foundation.
 PROFIBUS PROCESS FIELD BUS is a registered trademark of PROFIBUS NUTZERORGANISATION e.V.
 MODBUS is a registered trademark of Schneider Automation, Inc.
 SONARtrac and CiDRA are registered trademarks of CiDRA.

CiDRA
 50 Barnes Park North
 Wallingford, CT 06492
 Tel. +1.203.265.0035
 www.cidra.com

SONARtrac[®] Water and Wastewater Flow Measurement System Specifications

Parameter	Specifications	Comments
Pipe diameters	2" to 60" (50.8mm to 1524.0mm)	Metric and custom sizes available ^(a)
Flow velocity range	Liquid: 3 to 30 ft/s (0.91 to 19.1 m/s) ^(b)	Some flow conditions may permit flow measurements below 3 ft/sec ^(c)
Flow rate accuracy	±1.0% of reading	
Entrained Air Range	Not upgradeable to include Gas Volume Fraction (GVF) measurement	
Repeatability	±0.3% of reading	
Sensor head	Clamp-mounted onto the existing pipe section; designed for single, permanent installation Certified to IP55	2"-36" Sensor Length—34.7" (91.4cm) Over 36" Sensor— 51.2" (130.0cm) Height within flange diameter of pipe Lightweight (22 lbs./10 kg for 8" meter) Stainless Steel designed to IP55
Transmitter with integrated flow processor	Programmable by keypad or PC interface Self-diagnostics capability	
Operating Temperature Range:		
Transmitter	-4°F to +140°F (-20°C to +60°C)	Inquire with CiDRA for temperatures outside these specified ranges.
Sensor head process temp.	-40°F to +212°F (-40°C to +100°C)	
Sensor head ambient temp.	-40°F to +140°F (-40°C to +60°C)	
Storage Temperature Range:		
Transmitter	-22°F to +176°F (-30°C to +80°C)	
Sensor head	-40°F to +185°F (-40°C to +85°C)	
Cable between transmitter and sensor head	PLTC or armored cable with one end connectorized	Cable lengths up to 300ft (90m)
Analog input	Two (2) 4-20 mA	Enables internal logging of optional process parameters
Analog output	Two (2) isolated 4-20 mA current outputs	One (1) with HART [®] protocol
Digital outputs	Pulse output Alarm output	
Digital interfaces	10Base-T Ethernet USB/Memory Stick RS232 serial	
Communication interfaces	Standard: RS232/485 Optional: MODBUS [®] RTU/ASCII Optional: FOUNDATION Fieldbus [™] Optional: PROFIBUS [®] PA	
Transmitter local display	LCD with backlight	Provides flow rate, system status, system diagnostics
Data logging capability	Yes	
Transmitter enclosure	NEMA 4X , IP66	
Power requirements	AC version: 100 to 240 VAC, 50/60 Hz, 25 watts DC version: 18 to 36 VDC, 25 watts	
Area classification	Class 1 Division 2, Groups A-D Standard: General Purpose	
Altitude	5000 meters	Certified for high altitude regions
^(a) Inquire with CiDRA for availability and specifications on sizes greater than 36". ^(c) Inquire with CiDRA for qualifying your application under 3 feet/second ^(b) Minimum flow can be application dependent.		

Contact CiDRA

To speak with an applications engineer about CiDRA's SONARtrac systems or other CiDRA industrial process measurement solutions, call +1.203.265.0035 or visit our web site at www.cidra.com.

All information contained herein is believed to be accurate and is subject to change without notice. No responsibility is assumed for its use. Specifications are preliminary and CiDRA reserves the right to make changes, without notice to product designs, specifications, functions, components and manufacturing methods.

